

Cultivator Tines / Blades

CULTIVATOR TINES

COD.	kg	DIMENSION			HOLES	THICKNESS	
		A mm	B mm	C mm			
A	0F700	9,800	875	85	43	D.13	22
B	0F701	2,350	150	194	40/70	M12	10
C	0F702	1,750	120	235	-	M12	10
D	0F703	1,850	100	295	-	M12	8
F	0F705	2,400	110	300	-	M12	8
G	0F706	2,400	110	300	-	M12	8
H	0F707	2,035	349	130	70	M12	10
I	0F708	2,035	349	130	70	M12	10
M	0F709	2,100	349	130	70	M12	10
N	0F710	2,100	349	130	70	M12	10



DIAMETER D		THICKNESS		PLAIN DISC Weight		TOOTHED DISC Weight	
mm	inch	mm	inch	kg	lb	kg	lb
250	10"	2,5	6/64"	1,15	2,5	-	-
280	11"	2,5	6/64"	1,30	2,9	-	-
305	12"	2,5	6/64"	1,40	3,1	-	-
310	12"	4,5	11/64"	2,80	6,2	-	-
325	13"	2,5	6/64"	1,60	3,5	-	-
330	13"	2,5	6/64"	1,65	3,6	-	-
350	14"	3	8/64"	2,20	4,9	-	-
360	14"	4,5	11/64"	3,70	8,2	-	-
410	16"	3,2	8/64"	3,50	7,7	3,00	6,6
410	16"	6	15/64"	6,10	13,4	-	-
460	18"	3,2	8/64"	4,40	9,7	3,60	7,9
460	18"	3,5	9/64"	4,80	10,6	3,90	8,6
460	18"	6	15/64"	6,80	15,0	-	-
510	20"	3,5	9/64"	5,80	12,8	5,20	11,5
510	20"	4	10/64"	6,70	14,8	6,00	13,2
510	20"	4,5	11/64"	7,30	16,1	6,50	14,3
510	20"	5	13/64"	8,40	18,5	7,70	17,0
510	20"	6	15/64"	9,60	21,2	8,6	18,2
530	21"	4	10/64"	7,50	16,5	6,70	14,8
530	21"	6	15/64"	10,50	23,1	9,70	21,4
560	22"	4	10/64"	8,20	17,64	7,20	15,63
560	22"	4,5	11/64"	9,00	19,8	7,90	17,4
560	22"	5	13/64"	9,90	21,48	8,80	19,10
560	22"	6	15/64"	11,60	25,6	10,30	22,7
610	24"	5	13/64"	11,60	25,6	10,50	23,1
610	24"	6	15/64"	14,10	31,1	12,70	28,0
660	26"	5	15/64"	13,20	29,05	12,20	26,84
660	26"	6	15/64"	17,20	37,9	15,50	34,2
660	26"	7	18/64"	20,10	44,3	18,10	39,9
660	26"	8	20/64"	23,60	52,0	20,70	45,6
710	28"	6	15/64"	20,03	44,2	18,50	40,8
710	28"	7	18/64"	27,20	60,0	23,50	51,8
710	28"	8	20/64"	29,10	64,2	26,80	59,1
710	28"	10	25/64"	32,7	72,14	29,8	65,56
760	30"	8	20/64"	29,10	64,2	26,80	59,1
760	30"	10	25/64"	36,20	79,8	33,50	73,9
810	32"	8	20/64"	30	65	28	62
810	32"	10	25/64"	43	95	40	88
910	36"	12	30/64"	68	150	60	132

PLAIN DISC



NOTCHED DISC




DIAMETER AND RADIUS - CURVED DISC BULLDOG

DIAMETER D		R		STAMP CODE 047	
mm	inch	mm	inch	900 mm	
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
560	22"	61	2" 13/32	-	-
610	24"	73	2" 7/16	-	-
660	26"	87	3" 7/16	-	-
710	28"	102	4" 7/32	-	-
-	-	-	-	-	-



BULLDOG



DIAMETER, THICKNESS AND WEIGHT WAVED DISC TURBO

DIAMETER D		THICKNESS		Weight	
mm	inch	mm	inch	mm	inch
380	15"	4	5/32"	2,5	5,5
406	16"	4	5/32"	3,6	8,0
430	16" 59/64	4	5/32"	4,2	9,26
450	17" 23/32	5	15/64"	5,3	11,7
460	18"	4	5/32"	5,0	11,0
510	20"	4	5/32"	7,3	16,1
560	22"	5	15/64"	9,0	19,8



WAVED DISC WITH FLAT IN CENTER.

DIAMETER D		C		WELGHT		FLAT IN center P		N.Wave	HEIGHT Wave A	
mm	inch	mm	inch	kg	lb	mm	inch		mm	inch
470	18" 8/16	4	3/16	4,50	9,9	170	6" 11/16	8	45	1" 12/16
520	20" 8/16	5	3/16	8,40	18,5	170	6" 11/16	8	60	2" 6/16
520	20" 8/16	6	4/16	9,60	21,2	170	6" 11/16	8	60	2" 6/16
580	22" 13/16	5	3/16	8,20	18,1	220	8" 11/16	8	63	2" 8/16
580	22" 13/16	6	4/16	11,60	25,6	220	8" 11/16	8	63	2" 8/16
580	22" 13/16	7	4/16	13,50	29,8	220	8" 11/16	8	63	2" 8/16
630	24"	6	4/16	14,1	31,1	220	8" 11/16	8	63	2" 8/16

